

CNC Turbine/Roll Lathe WALDRICH SIEGEN, Model DH 1600/35 CNC x 12000-1 YOM 1989, with hydrostatic guide ways in z and x axis, initial start up 4/1990 option: new 3 axis CNC control SINUMERIK 840 DsL, new electric, new wiring, new tail stock, ser. no. 13.152



machine at production place GE in Birr/Switzerland the machine was only used in finishing of turbine shafts and is in a new mechanical condition.

We do guarantee a new machine accuracy!

techn. details

- Hydrostatic guide ways in z axis
- Hydrostatic guide ways in x axis
- Hydrostatic worm drive in z axis
- C axis in face plate
- Workpiece measuring in upper carriage

Specialized in used heavy machine tools from WALDRICH SIEGEN WALDRICH COBURG Dipl. Ing. Elmar Ernst Industrieanlagen GmbH Hüttenfeld 8 (street) D - 51427 Bergisch Gladbach (city) GMBH Tel.+49 2204 9844010 Fax +49 2204 9844011 mob +49 172 1520295 email: maschinen@web.de www.ernstmachines.de

working area		
max. turning-∅ over saddle	mm	1.600
distance between centers	mm	12.000
max. work piece lengths	mm	11.800
max. work piece weight	t	40

head stock		
power at main spindle	kW	136
revs at face plate	min-1	1 – 240
step 1	min-1	1 – 60
step 2	min-1	4 – 240
base speed	min-1	15

face plate with C axis with clamping system		
face plate - \varnothing	mm	1.200
clamping area outside, min – max	mm	105 – 1.000
no. of clamping jaws	no.	4
max. torque at face plate	Nm	80.000
center angle	degree	60

carriage		
no. of carriages	no	1
travel way Z - axis	mm	13.500
travel way X - axis	mm	700
traverse X - axis	mm/min	0 - 4.500
traverse Z - axis	mm/min	0 - 4.500
rapid traverse X - axis	mm/min	4.500
rapid traverse Z - axis	mm/min	4.500
upper carriage with measurement system for work pieces		

The machine doesn't have a tailstock, because the user produced the turbine shafts on 2 stadies

Option 1: a new tailstock

tailstock		
dia. of quill	mm	360
movement of quill	mm	100

measurements		
machine lengths	mm	20.000
machine widths	mm	5.000
machine heights, above floor level	mm	2.400
machine weight	t	105
electrical conditions	V/Hz	380/50

hydrostatic steadies		
no. of steadies	no.	2
clamping area	mm	125 - 650
max. work piece weight	t	20
no. of quills	no.	3
rapid traverse	mm/min	2.150

accessories

- 1 piece of chip conveyor
- 2 pieces of hydrostatic steadies, with 3 quill, 20 t each, 200 650 mm
- 1 piece conventional steady
- 1 integrated measurement system in upper carriage for workpiece measurement integrated C axis in face plate with clamping

delivery conditions

delivery time

the machine as/where is direct after order remanufacturing and assembly after 5 month

payment

100 % for the machine as/where is via irrevocable LC

70 % down payment for the option

20 % at beginning of installation

10 % after commissioning against a bank guarantee

With best regards



upper carriage with tool holder and work piece measurement






headstock, face plate with C axis and clamping, hydrostatic steady



used as turbine rotor finish lathe



hydrostatic steadies with 3 quills per steady



hydrostatic guide ways in X and Z axis



hydrostatic worm drive for the carriage



guide ways and hydrostatic worm drive like new



the machine was only used in finishing and is in a new mechanical condition.

we guarantee a new machine accuracy!



option 1: new tailstock



machine stored in our warehouse in Freudenberg



machine in top condition, like new



option 2: new CNC control SINUMERIK 840 DsL



option 2: new electric cabinet



take high way no. 45 (Dortmund to Gambacher Cross), exit Freudenberg, from direction Dortmund, turn left, at the traffic light turn left, then direct left again, from direction Gambacher Cross, turn right, at the traffic light turn left, then direct left again, Spedition Bender, first building on the left side, door 24